

DOWNLIGHT HEKTOR 2 827 27W 45° WHITE | ON/OFF

Article number: N213-K0003-RF827-H8-H45-ZC02_700-S6-###



LED	COB
Light colour	2700 [K]
CRI	80
Led chip flux	3772 [lm]
Luminous flux	3017 [lm]
System power	27 [W]
Luminaire Efficiency	112 [lm/W]
Beam angle	45°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	1,1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 16.07.2024



+48 32 388 80 00



www.corapl
cora@corapl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska