

DOWNLIGHT

DOWNLIGHT HEKTOR 2 827 31W 60° WHITE | ON/OFF

COB

80

2700 [K] |

4311 [lm]

3448 [lm]

111 [lm/W]

ON/OFF

3 SDCM

31 [W]

60°

Article number: N213-K0003-RF827-H8-H60-ZC03_800-S6-###



cutout Ø160mm

Down	light	LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

1	111	M	IN	Δ	R	F

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

IWIINAINE				
1,1 [kg]				
IP 20, IK 3,				
WHITE				
Glass				
220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 18.05.2024