

DOWNLIGHT

## DOWNLIGHT HEKTOR 2 930 19W 60° WHITE | ON/OFF

COB

90

3000 [K] |

2305 [lm]

1844 [lm]

19 [W] 97 [lm/W]

60°

ON/OFF

3 SDCM

Article number: N213-K0003-RF930-H8-H60-ZC01\_500-S6-###



cutout Ø160mm

Deven	1 In .	
Down	lign	ιιευ
	· ·	

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

1	ш	М	IN	Δ	IR	F

Controller

MacAdam

Light colour

Led chip flux

Luminous flux

System power

Luminaire Efficiency Beam angle

CRI

JMINAINE				
Weight	1,1 [kg]			
Protection rating IP , IK , class	IP 20, IK 3,			
Luminaire colour	WHITE			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			
Operating voltage	220-2401 30-00112			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 18.05.2024