

DOWNLIGHT

DOWNLIGHT HEKTOR 2 930 27W 60° WHITE | ON/OFF

COB

90

3000 [K] |

3227 [lm]

2581 [lm]

96 [lm/W]

ON/OFF

3 SDCM

27 [W]

60°

Article number: N213-K0003-RF930-H8-H60-ZC02_700-S6-###



cutout Ø160mm

Deven	1 I.e.	
Down	lign	ιιευ
	<u> </u>	

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LU	JM	IIN	AI	R	E

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024