

## DOWNLIGHT HEKTOR 2 930 35W 60° WHITE | ON/OFF

Article number: N213-K0003-RF930-H8-H60-ZC03\_900-S6-###



LED	COB
Light colour	3000 [K]
CRI	90
Led chip flux	4150 [lm]
Luminous flux	3320 [lm]
System power	35 [W]
Luminaire Efficiency	95 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 1,1 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour Glass
Cover 220-240V 50-6

Cover 220-240V 50-60Hz

Operating voltage

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska