

## DOWNLIGHT HEKTOR 2 940 27W 45° WHITE | ON/OFF

Article number: N213-K0003-RF940-H8-H45-ZC02\_700-S6-###



COB Light colour 4000 [K] | CRI Led chip flux 3383 [lm] Luminous flux 2706 [lm] System power 27 [W] Luminaire Efficiency 100 [lm/W] Beam angle 45° Controller ON/OFF MacAdam 3 SDCM

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 1,1 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 18.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska