

## DOWNLIGHT HEKTOR 2 825 25W 15° WHITE BREAD ON/OFF

COB

80

3042 [lm]

2433 [lm]

97 [lm/W]

ON/OFF

3 SDCM

25 [W]

15°

2500 [K] BREAD

Article number: N213-K0003-VF825-H8-H15-ZC02\_650-S6-###



Ø160mm

Downlight LE	D
--------------	---

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LU	JN	IIN	A	R	E

Light colour CRI

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	1,1 [kg]	
Protection rating IP , IK , class	IP 20, IK 3,	
Luminaire colour	WHITE	
Cover	Glass	
Operating voltage	220-240V 50-60Hz	

may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features