

## DOWNLIGHT CYGNUS Z1 930 14W 60° BLACK HI EFFICIENT ON/OFF

Article number: N214-K0002-BB930-H8-H60-ZC01\_350-S6-###



COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 2256 [lm] Luminous flux 1804 [lm] System power 14 [W] Luminaire Efficiency 129 [lm/W] Beam angle 60° Controller ON/OFF MacAdam 3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Available in white and black. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 2,05 [kg]

Protection rating IP, IK, class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements  $\pm -10\%$  System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00



Generated: 29.06.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska