

DOWNLIGHT CYGNUS Z1 957 10W 45° BLACK SPECIAL ON/OFF

45°

Article number: N214-K0002-CC957-H8-H45-ZC01_250-S6-###



 LED
 COB

 Light colour
 5700 [K] SPECIAL

 CRI
 90

 Led chip flux
 1318 [lm]

 Luminous flux
 1054 [lm]

 System power
 10 [W]

 Luminaire Efficiency
 105 [lm/W]

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Beam angle

 Weight
 2,05 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white and black. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska