


DOWNLIGHT CYGNUS Z1 930 21W 45° BLACK CRI97 ON/OFF

Article number: N214-K0002-HI930-H8-H45-ZC02_550-S6-###





LED	СОВ
Light colour	3000 [K] CRI97
CRI	90
Led chip flux	2402 [lm]
Luminous flux	1921 [lm]
System power	21 [W]
Luminaire Efficiency	91 [lm/W]
Beam angle	45°
Controller	ON/OFF
MacAdam	3 SDCM

2,05 [kg]

BLACK

Glass

IP 20, IK 3,

220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white and black. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024