DOWNLIGHT CYGNUS Z1 850 10W 60° BLACK | ON/OFF

Article number: N214-K0002-RF850-H8-H60-ZC01_250-S6-###

157

205*205

cut out Ø190x190mm

LED	COB
Light colour	5000 [K]	
CRI	80
Led chip flux	1447 [lm]
Luminous flux	1157 [lm]
System power	10 [W]
Luminaire Efficiency	116 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white and black. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight	2,05 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

CE EHI UK CA

+48 32 388 80 00

www.cora.pl
cora@cora.pl

Street: Ignatza Hakuby 18
41-914 Bytom, Polska