


## DOWNLIGHT

## DOWNLIGHT CYGNUS Z2 930 62W 30° GREY HI EFFICIENT ON/OFF

Article number: N215-K0001-BB930-H8-H30-ZC03\_800-S6-###







D	own		t LED
		· ·	

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux	
Luminous flux	9912 [lm]
System power	7929 [lm]
Luminaire Efficiency	62 [W]
	128 [lm/W]
Beam angle	30°
Controller	ON/OFF
MacAdam	
	3 SDCM

## LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl 0

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024