


DOWNLIGHT CYGNUS Z2 940 62W 45° GREY HI EFFICIENT ON/OFF

Article number: N215-K0001-BB940-H8-H45-ZC03_800-S6-###







Down	light	LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LED	СОВ
Light colour	4000 [K] HI EFFICIENT
CRI	
Led chip flux	90
Luminous flux	9928 [lm]
System power	7942 [lm]
Luminaire Efficiency	62 [W]
Deem engle	128 [lm/W]
Beam angle	45°
Controller	
MacAdam	ON/OFF
indo locin	3 SDCM

LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024