


DOWNLIGHT CYGNUS Z2 957 74W 30° GREY SPECIAL ON/OFF

Article number: N215-K0001-CC957-H8-H30-ZC03_950-S6-###



3 SDCM





COB 5700 [K] SPECIAL Light colour CRI Led chip flux 9180 [lm] Luminous flux 7344 [lm] System power 74 [W] Luminaire Efficiency 99 [lm/W] Beam angle 30° Controller ON/OFF

LUMINAIRE

MacAdam

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 14.08.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska