

DOWNLIGHT CYGNUS Z2 930 50W 60° GREY PREMIUM COLOR ON/OFF

Article number: N215-K0001-PC930-HA-H60-ZC02_650-S6-###





LED COB

Light colour 3000 [K] PREMIUM COLOR

CRI

90 ed chip flux

 Led chip flux
 5552 [lm]

 Luminous flux
 4441 [lm]

 System power
 50 [W]

 Luminaire Efficiency
 89 [lm/W]

 Beam angle
 60°

 Controller
 60°

Controller

MacAdam

3 SDCM

LUMINAIRE

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska