


DOWNLIGHT

DOWNLIGHT CYGNUS Z2 830 74W 45° GREY | ON/OFF

Article number: N215-K0001-RF830-H8-H45-ZC03_950-S6-###



COR





MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	45°
Luminaire Efficiency	112 [lm/W]
System power	74 [W]
Luminous flux	8275 [lm]
Led chip flux	10344 [lm]
CRI	80
Light colour	3000 [K]
LED	COB

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska