

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 835 62W 45° GREY | ON/OFF

Article number: N215-K0001-RF835-H8-H45-ZC03_800-S6-###




2,8 [kg]

GREY

Glass

IP 20, IK 3,

220-240V 50-60Hz





| Downlight LED |
|-------------------|
| LED downlight for |

| LED | СОВ |
|----------------------|------------|
| Light colour | 3500 [K] |
| CRI | 80 |
| Led chip flux | 8906 [lm] |
| Luminous flux | 7124 [lm] |
| System power | 62 [W] |
| Luminaire Efficiency | 115 [lm/W] |
| Beam angle | 45° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024