


# DOWNLIGHT CYGNUS Z2 850 74W 60° GREY | ON/OFF

Article number: N215-K0001-RF850-H8-H60-ZC03\_950-S6-###



LED	COB
Light colour	5000 [K]
CRI	80
Led chip flux	11004 [lm]
Luminous flux	8803 [lm]
System power	74 [W]
Luminaire Efficiency	119 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

### LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.corra.pl  
cora@corra.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska