

DOWNLIGHT

## DOWNLIGHT CYGNUS Z2 927 42W 15° GREY | ON/OFF


Article number: N215-K0001-RF927-H8-H15-ZC02\_550-S6-###



COB

80

2700 [K] |





Dov	nliq	ht Ll	ED
201			

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

UMINAIRE			
MacAdam	3 SDCM		
Controller	ON/OFF		
Beam angle	15°		
Luminaire Efficiency	93 [lm/W]		
System power	42 [W]		
Luminous flux	3910 [lm]		
Led chip flux	4888 [lm]		

## L

Light colour

CRI

Weight	2,8 [kg]			
Protection rating IP , IK , class	IP 20, IK 3,			
Luminaire colour	GREY			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			

## may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features