

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 927 38W 45° GREY | ON/OFF

Article number: N215-K0001-RF927-H8-H45-ZC01_500-S6-###



COB

80

2700 [K] |

4444 [lm]

3555 [lm]


94 [lm/W]

ON/OFF

3 SDCM

38 [W]

45°





Downlight LED)
---------------	---

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LU	MI	NΑ	IR	E

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE							
Weight	2,8 [kg]						
Protection rating IP , IK , class	IP 20, IK 3,						
Luminaire colour	GREY						
Cover	Glass						
Operating voltage	220-240V 50-60Hz						

may	change	VVILII	produc	impic	venieni	s uue	10	lecinical	auva	nce

Note: All data are typical values. Tolerance of measurements +/-10% System features

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024