

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 927 46W 45° GREY | ON/OFF

Article number: N215-K0001-RF927-H8-H45-ZC02_600-S6-###



COB

80

2700 [K] |

5334 [lm]

4267 [lm]


93 [lm/W]

ON/OFF

3 SDCM

46 [W]

45°





LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

| LU | MI | NΑ | IR | E |
|----|----|----|----|---|

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| JMINAIRE | | | | | |
|-----------------------------------|------------------|--|--|--|--|
| Weight | 2,8 [kg] | | | | |
| Protection rating IP , IK , class | IP 20, IK 3, | | | | |
| Luminaire colour | GREY | | | | |
| Cover | Glass | | | | |
| Operating voltage | 220-240V 50-60Hz | | | | |
| | | | | | |

| may change | with product | improvements | uue io | lecinical | auvances |
|------------|--------------|--------------|--------|-----------|----------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

Note: All data are typical values. Tolerance of measurements +/-10% System features

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024