


DOWNLIGHT

DOWNLIGHT CYGNUS Z2 930 38W 15° GREY | ON/OFF

Article number: N215-K0001-RF930-H8-H15-ZC01_500-S6-###







UMINAIRE		
MacAuam	3 3DCIVI	
MacAdam	3 SDCM	
Controller	ON/OFF	
Beam angle	15°	
Luminaire Efficiency	97 [lm/W]	
System power	38 [W]	
Luminous flux	3688 [lm]	
Led chip flux	4610 [lm]	
CRI	90	
Light colour	3000 [K]	
LED	COB	

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LU **/INAIRE**

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska