


DOWNLIGHT CYGNUS Z2 930 68W 45° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB930-H8-H45-ZC03_900-S6-###







Light colour3000 [K] HI EFFICIENTCRI90Led chip flux11046 [m]Luminous flux8836 [m]System power68 [W]Luminaire Efficiency130 [m/W]Beam angle45°ControllerON/OFFMacAdam3 SDCM	LED	COB
Led chip flux90Luminous flux11046 [lm]System power8836 [lm]Luminaire Efficiency68 [W]Beam angle130 [lm/W]Beam Angle45°Controller0N/OFFMacAdam0		
Luminous flux11046 [lm]System power8836 [lm]Luminaire Efficiency68 [W]Beam angle130 [lm/W]Controller45°MacAdamON/OFF		90
System power8836 [lm]Luminaire Efficiency68 [W]Beam angle130 [lm/W]Controller45°MacAdamON/OFF		11046 [lm]
Luminaire Efficiency 68 [W] Beam angle 130 [lm/W] Controller 45° MacAdam ON/OFF		8836 [lm]
130 [lm/W] Beam angle 45° Controller MacAdam		68 [W]
Controller ON/OFF		130 [lm/W]
MacAdam	Controller	
3 SDCM	MacAdam	
		3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska