


DOWNLIGHT CYGNUS Z2 935 62W 15° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB935-H8-H15-ZC03_800-S6-###







COB 3500 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 9446 [lm] Luminous flux 7556 [lm] System power 62 [W] Luminaire Efficiency 122 [lm/W] Beam angle 15° Controller

LUMINAIRE

MacAdam

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 26.06.2024



+48 32 388 80 00



ON/OFF

3 SDCM

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska