


DOWNLIGHT CYGNUS Z2 935 54W 30° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB935-H8-H30-ZC02_700-S6-###







 LED
 COB

 Light colour
 3500 [K] HI EFFICIENT

 CRI
 90

 Led chip flux
 8362 [Im]

 Luminous flux
 6689 [Im]

 System power
 54 [W]

 Luminaire Efficiency
 124 [Im/W]

 Beam angle
 30°

Beam angle 30°
Controller
MacAdam 3 SDCM

LUMINAIRE

Weight 2,8 [kg]

Protection rating IP, IK, class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska