


DOWNLIGHT CYGNUS Z2 935 50W 60° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB935-H8-H60-ZC02_650-S6-###





LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	90
Led chip flux	
Luminous flux	7808 [lm]
System power	6246 [lm]
Luminaire Efficiency	50 [W]
Beam angle	125 [lm/W]
Controller	60°
MacAdam	ON/OFF
	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

