


## DOWNLIGHT CYGNUS Z2 940 68W 15° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB940-H8-H15-ZC03\_900-S6-###



3 SDCM





COB 4000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 11064 [lm] Luminous flux 8851 [lm] System power 68 [W] Luminaire Efficiency 130 [lm/W] Beam angle 15° Controller ON/OFF MacAdam

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

## LUMINAIRE

Weight 2,8 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements  $\pm -10\%$  System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska