

## DOWNLIGHT CYGNUS Z2 940 54W 30° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB940-H8-H30-ZC02\_700-S6-###







**Downlight LED** 

COB 4000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 8770 [lm] Luminous flux 7016 [lm] System power 54 [W] Luminaire Efficiency 130 [lm/W] Beam angle 30° Controller

# enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

#### LUMINAIRE

MacAdam

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



ON/OFF

3 SDCM

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska