


DOWNLIGHT CYGNUS Z2 940 68W 30° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB940-H8-H30-ZC03_900-S6-###







_				_
Dow	nlia	ht	I FI	D
				-

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

UMINAIRE			
nico noci il	3 SDCM		
MacAdam	ON/OFF		
Controller	30°		
Beam angle	130 [lm/W]		
Luminaire Efficiency	68 [W]		
System power	8851 [lm]		
Luminous flux	11064 [lm]		
Led chip flux	90		
CRI	EFFICIENT		
Light colour	4000 [K] HI		
LED	СОВ		

LU

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

