

DOWNLIGHT CYGNUS Z2 940 20W 60° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB940-H8-H60-ZC01_250-S6-###





Ø365x190mm

| COB | Downlight LED |
|--------------------------|---|
| 4000 [K] HI EFFICIENT | LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing |
| 90 | enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W |

3250 [lm]

2600 [lm]

130 [lm/W]

ON/OFF

3 SDCM

20 [W]

60°

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| Weight | 2,8 [kg] | |
|-----------------------------------|------------------|--|
| Protection rating IP , IK , class | IP 20, IK 3, | |
| Luminaire colour | BLACK | |
| Cover | Glass | |
| Operating voltage | 220-240V 50-60Hz | |

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

| Protection rating IP, IK, class | IP 20, IK 3, |
|---------------------------------|------------------|
| Luminaire colour | BLACK |
| Cover | Glass |
| Operating voltage | 220-240V 50-60Hz |
| | |

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska