

DOWNLIGHT CYGNUS Z2 940 46W 60° BLACK HI EFFICIENT ON/OFF

Article number: N215-K0002-BB940-H8-H60-ZC02_600-S6-###







D	own	liaht	LED
_			

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LED	COB		
Light colour	4000 [K] HI		
CRI	EFFICIENT		
Led chip flux	90		
Luminous flux	7586 [lm]		
System power	6068 [lm]		
	46 [W]		
Luminaire Efficiency	132 [lm/W]		
Beam angle	60°		
Controller			
MacAdam	ON/OFF		
	3 SDCM		
UMINAIRE			

LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska