


DOWNLIGHT CYGNUS Z2 930 50W 15° BLACK PREMIUM WHITE ON/OFF

Article number: N215-K0002-HE930-HA-H15-ZC02_650-S6-###







LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 7318 [lm]

 Luminous flux
 5854 [lm]

 System power
 50 [W]

 Luminaire Efficiency
 117 [lm/W]

 Beam angle
 15°

Controller

ON/OFF

MacAdam

3 SDCM

LUMINAIRE

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska