

DOWNLIGHT CYGNUS Z2 930 74W 15° BLACK PREMIUM COLOR ON/OFF

Article number: N215-K0002-PC930-HA-H15-ZC03_950-S6-###







COB

3000 [K] PREMIUM COLOR Light colour

CRI

90 Led chip flux 7654 [lm] Luminous flux 6123 [lm] System power 74 [W] Luminaire Efficiency 83 [lm/W] Beam angle 15° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 2,8 [kg] Protection rating IP, IK, class IP 20, IK 3, WHITE Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska