

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 830 54W 30° BLACK | ON/OFF

Article number: N215-K0002-RF830-H8-H30-ZC02_700-S6-###





LED	COB
Light colour	3000 [K]
CRI	80
Led chip flux	7622 [lm]
Luminous flux	6097 [lm]
System power	54 [W]
Luminaire Efficiency	113 [lm/W]
Beam angle	30°
Controller	ON/OFF
MacAdam	3 SDCM
UMINAIRE	

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

L

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska