

DOWNLIGHT

## DOWNLIGHT CYGNUS Z2 835 54W 15° BLACK | ON/OFF

COB


80

3500 [K] |

7792 [lm]

Article number: N215-K0002-RF835-H8-H15-ZC02\_700-S6-###







| Down | ligh | t L | ED |
|------|------|-----|----|
|      |      |     |    |

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

| LUMINAIRE |                      |            |  |  |
|-----------|----------------------|------------|--|--|
|           | MacAdam              | 3 SDCM     |  |  |
|           | Controller           | ON/OFF     |  |  |
|           | Beam angle           | 15°        |  |  |
|           | Luminaire Efficiency | 115 [lm/W] |  |  |
|           | System power         | 54 [W]     |  |  |
|           | Luminous flux        | 6233 [lm]  |  |  |
|           |                      |            |  |  |

| LU | JM | IN | AI | R | E |
|----|----|----|----|---|---|

**OPTIONS** 

Light colour

Led chip flux

CRI

| Weight                            | 2,8 [kg]         |
|-----------------------------------|------------------|
| Protection rating IP , IK , class | IP 20, IK 3,     |
| Luminaire colour                  | BLACK            |
| Cover                             | Glass            |
| Operating voltage                 | 220-240V 50-60Hz |
|                                   |                  |

## RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

## (€ III ĽK

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.