


DOWNLIGHT CYGNUS Z2 835 74W 15° BLACK | ON/OFF

Article number: N215-K0002-RF835-H8-H15-ZC03_950-S6-###







COB Light colour 3500 [K] | CRI Led chip flux 10576 [lm] Luminous flux 8460 [lm] System power 74 [W] Luminaire Efficiency 114 [lm/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska