

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 835 28W 30° BLACK | ON/OFF

COB

80

3500 [K] |

3896 [lm]

3116 [lm]

111 [lm/W]

ON/OFF

3 SDCM

28 [W]

30°

Article number: N215-K0002-RF835-H8-H30-ZC01_350-S6-###







Down	light	LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

	MacAdam	
_		

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

Luminaire Efficiency

CRI

LUMINAIRE	
Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024