


DOWNLIGHT

DOWNLIGHT CYGNUS Z2 835 20W 45° BLACK | ON/OFF

Article number: N215-K0002-RF835-H8-H45-ZC01_250-S6-###







COB
3500 [K]
80
2782 [lm]
2225 [lm]
20 [W]
111 [lm/W]

45°

ON/OFF

3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE

Light colour

Led chip flux Luminous flux System power Luminaire Efficiency

Beam angle

Controller

MacAdam

CRI

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024