

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 840 46W 15° BLACK | ON/OFF


COB

80

4000 [K] |

Article number: N215-K0002-RF840-H8-H15-ZC02_600-S6-###







Downl	lial	ht I		
Downi	IC	ш	ᇆ	U.

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE			
MacAdam	3 SDCM		
Controller	ON/OFF		
Beam angle	15°		
Luminaire Efficiency	119 [lm/W]		
System power	46 [W]		
Luminous flux	5451 [lm]		
Led chip flux	6814 [lm]		

LUMINAIRE	
Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Light colour

CRI

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024