

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 850 50W 15° BLACK | ON/OFF

COB

5000 [K] |

Article number: N215-K0002-RF850-H8-H15-ZC02_650-S6-###





Down	liał	nt L	ED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

MacAdam		3 SDCM
Controller		ON/OFF
Beam angle		15°
Luminaire Efficient	су	120 [lm/W]
System power		50 [W]
Luminous flux		6022 [lm]
Led chip flux		7528 [lm]
CRI		80

LUMINAIRE

Light colour

Weight	2,8 [kg]	
Protection rating IP , IK , class	IP 20, IK 3,	
Luminaire colour	BLACK	
Cover	Glass	
Operating voltage	220-240V 50-60Hz	

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features