

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 850 46W 60° BLACK | ON/OFF

COB

80

5000 [K] |

6950 [lm]

5560 [lm]

121 [lm/W]

ON/OFF

3 SDCM

46 [W]

60°

Article number: N215-K0002-RF850-H8-H60-ZC02_600-S6-###





D	1. A.	
Down	llanı	I LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

	MacAdam
_	

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

Luminaire Efficiency

CRI

LUMINAIRE		
2,8 [kg]		
IP 20, IK 3,		
BLACK		
Glass		
220-240V 50-60Hz		

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024