

### DOWNLIGHT

# DOWNLIGHT CYGNUS Z2 930 70W 45° BLACK | ON/OFF

Article number: N215-K0002-RF930-H8-H45-ZC03\_900-S6-###



8300 [lm]

6640 [lm]

95 [lm/W]

ON/OFF

3 SDCM

70 [W]

45°





COB	Downlight
3000 [K]	LED down
90	white, blac

#### nt LED

nlight for drop ceiling istallation. Aluminium housing. Available in ck and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

## LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

## Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska