

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 940 54W 60° BLACK | ON/OFF

Article number: N215-K0002-RF940-H8-H60-ZC02_700-S6-###







| JMINAIRE | |
|----------------------|------------|
| MacAdam | 3 SDCM |
| Controller | ON/OFF |
| Beam angle | 60° |
| Luminaire Efficiency | 100 [lm/W] |
| System power | 54 [W] |
| Luminous flux | 5412 [lm] |
| Led chip flux | 6766 [lm] |
| CRI | 90 |
| Light colour | 4000 [K] |
| LED | COB |

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE

| Weight | 2,8 [kg] |
|-----------------------------------|------------------|
| Protection rating IP , IK , class | IP 20, IK 3, |
| Luminaire colour | BLACK |
| Cover | Glass |
| Operating voltage | 220-240V 50-60Hz |
| | |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024