

## DOWNLIGHT

## DOWNLIGHT CYGNUS Z2 825 42W 45° BLACK BREAD ON/OFF

СОВ


80

5148 [lm]

2500 [K] BREAD

Article number: N215-K0002-VF825-H8-H45-ZC02\_550-S6-###







Downlight LED
---------------

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

UMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	45°
Luminaire Efficiency	98 [lm/W]
System power	42 [W]
Luminous flux	4118 [lm]

LU	M	INA	ΑIF	RΕ.

**OPTIONS** 

Light colour CRI

Led chip flux

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

may change with product improvements due to technical advances.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 19.05.2024