

## DOWNLIGHT CYGNUS Z2 930 54W 15° WHITE HI EFFICIENT ON/OFF

Article number: N215-K0003-BB930-H8-H15-ZC02\_700-S6-###





COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 8756 [lm] Luminous flux 7004 [lm] System power 54 [W] Luminaire Efficiency 130 [lm/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

## LUMINAIRE

Weight 2,8 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska