

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 930 54W 30° WHITE HI EFFICIENT ON/OFF


Article number: N215-K0003-BB930-H8-H30-ZC02_700-S6-###



COB

90

3000 [K] HI EFFICIENT





Down	light	LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Led chip flux	90
Luminous flux	8756 [lm]
System power	7004 [lm]
	54 [W]
Luminaire Efficiency	130 [lm/W]
Beam angle	30°
Controller	
MacAdam	ON/OFF
	3 SDCM

LUMINAIRE

Light colour

CRI

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	Glass
Cover	220-240V 50-60Hz
Operating voltage	

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska