


DOWNLIGHT

DOWNLIGHT CYGNUS Z2 935 46W 30° WHITE HI EFFICIENT ON/OFF

Article number: N215-K0003-BB935-H8-H30-ZC02_600-S6-###







Down	light	LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Controller	ON/OFF
Controller	
Beam angle	30°
Luminaire Efficiency	126 [lm/W]
System power	46 [W]
	5798 [lm]
Luminous flux	7248 [lm]
Led chip flux	90
CRI	EFFICIENT
Light colour	3500 [K] HI
LED	COB

LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl 0

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024