


## DOWNLIGHT

## DOWNLIGHT CYGNUS Z2 935 54W 30° WHITE HI EFFICIENT ON/OFF

Article number: N215-K0003-BB935-H8-H30-ZC02\_700-S6-###







-		1.1.1	A	1.00	-
D	owi	זוו	nτ	LE	D

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	
Led chip flux	90
Luminous flux	8362 [lm]
System power	6689 [lm]
Luminaire Efficiency	54 [W]
·	124 [lm/W]
Beam angle	30°
Controller	ON/OFF
MacAdam	
	3 SDCM

## LUMINAIRE

Weight	2,8 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl  $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024