

DOWNLIGHT CYGNUS Z2 940 72W 15° WHITE HI EFFICIENT ON/OFF

Article number: N215-K0003-BB940-H8-H15-ZC03_950-S6-###







COB 4000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 11622 [lm] Luminous flux 9297 [lm] System power 72 [W] Luminaire Efficiency 129 [lm/W] Beam angle 15° Controller ON/OFF

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

LUMINAIRE

MacAdam

Weight 2,8 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



3 SDCM

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska