


DOWNLIGHT CYGNUS Z2 942 20W 45° WHITE MEAT WHITE ON/OFF

Article number: N215-K0003-CC942-H8-H45-ZC01_250-S6-###







LED COB
Light colour 4200 [K] MEAT WHITE

CRI 90

Led chip flux
2046 [lm]
Luminous flux

System power

Luminaire Efficiency

Beam angle

1636 [Im]

20 [W]

82 [Im/W]

Controller

MacAdam

3 SDCM

LUMINAIRE

 Weight
 2,8 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 19.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska